Like its big brother, the 2300, the Osburn 1500 has a high-quality 1/8" stainless steel baffle. With its 55,000 BTU/hr performance and compact firebox, this stove is easy to light, providing quick heat. In addition, its reduced exterior dimensions and minimal clearance requirements make it an ideal choice for small spaces. The 1500 model is part of our new, easy to identify family of wood stoves with doors bearing the Osburn logo.

1500



1500 with brushed nickel door



1500 with gold door





## Features

| Heating capacity                   | 500 to 1500 sq. ft.*           |
|------------------------------------|--------------------------------|
| Firebox volume                     | 1,5 cu. ft.                    |
| BTU/hr., EPA test wood             | 44,000                         |
| BTU/hr., seasoned cord wood        | 55,000                         |
| Exterior dimensions                | 27 1/2"H x 25 1/2"W x 20 1/2"D |
| Maximum log length                 | 19"                            |
| Ultra-quiet blower with variable s | speed Standard                 |
| Ash drawer with safety lid         | Standard                       |
| Mobile home approved               | Yes                            |

## **Options**

| Door; painted black, gold or brushed nickel plate | d  |
|---|----|
| Thermodisc for blower                             | r  |
| Adapter for fresh air kit (5" diameter            | r) |

1500 with black door